

# Move forward to big things. Clipsal Avanti.

Features and benefits include:

•

•

.

Large, smooth action switches

that are easy to operate

1, 2 or 3 gang configuration

Coloured LED's for load status

C-Bus programmable.



including residential homes.

Clipsal have really covered all bases with CIIDSAI NAVE FEAILY COVERED AII DASES WITH existent Downon Discovered AII DASES WITH Down CBUS AVANTI Chuisched the introduction of the new cross Avanti Switch Range. Clipsal's Avanti Switches and incorrorate Switch Mange. Chosais Avant Switches

are cous programmatice and mag

The unique iunous owners owner iunque in the unique ion of the iungue in the iungue of the iungue of

Avanti Range has a low profile architectural in a in index of the structure of the structu Avanti Range has a low profile architectura disabled and is ideal for all of the architectura including residential homes applications,

clipsal.com



#### **Installer Benefits**

- Standard pattern wall mounting (horizontal configuration only)
- Learn mode capabilities
- **Programmable Scenes**
- Configurable LED status indication.
- **User Benefits**
- Large rocker switch for aged care or disabled applications
  - Coloured LED load status indicators
  - 1,2 or 3 gang configuration.

## **Specifications**

Parameter	Description		
C-Bus voltage	15 to 36V DC, 18mA for normal operation. Does not provide current to C-Bus network.		
C-Bus AC input impedance	3.75kV RMS from C-Bus to mains (provided externally to 509xNL series unit)		
Maximum number of units per network	100		
Control functions	Load switching, dimming, timers and scene control		
Status indicators	User configurable red and green		
Warm-up time	5 seconds		
C-Bus connection	One terminal block to accommodate 0.2 to 1.3mm <sup>2</sup> (24 to 16 AWG)		
Operating temperature range	0 to 45° C		
Operating humidity range	10 to 95% Relative humidity		
Dimensions (W x H x D)	121 x 82 x 29mm		
Protrusion from wall	13mm		
Mounting centres	84mm		
Weight	5091NL	5092NL	5093NL
	87g	89g	91g

#### **Product range**

1 Button, C-Bus Large Rocker Switch	5091NL, WE
2 Button, C-Bus Large Rocker Switch	5092NL, WE
3 Button, C-Bus Large Rocker Switch	5093NL, WE

### **Product of Clipsal Australia Pty Ltd**

A member of the Schneider Electric Group

**Head Office** 

12 Park Terrace, Bowden South Australia 5007 Telephone (08) 8269 0511 Facsimile (08) 8340 1724 Internet clipsal.com E-Mail plugin@clipsal.com.au

**National Customer Service Enquiries:** 1300 2025 25

National Customer Service Facsimile: 1300 2025 56

printed on recycled paper CLIPCOM 14805 April 2008

International Enquiries International Sales and Marketing Telephone + 61 8 8269 0587 Facsimile + 61 8 8340 7350 E-Mail export@clipsal.com.au

New Zealand Clipsal Industries (NZ) Ltd Telephone (09) 576 3403 Facsimile (09) 576 1015 E-Mail headoffice@clipsal.co.nz

**Customer Service** Free Fax (0508) 250 305 Auckland/Mobile Phone (09) 572 0014 Free Phone (0508) CLIPSAL 2547725



You can find this brochure and many others online in PDF format at: clipsal.com Follow the links off the home page or access the following page directly: clipsal.com/wat\_lib\_pdf.cfm



Clipsal Australia Pty Ltd reserves the right to change specifications, modify designs and discontinue items without incurring obligation and whilst every effort is made to ensure that descriptions, specifications and other information in this catalogue are correct, no warranty is given in respect thereof and the company shall not be liable for any error therein. C3-007

© Clipsal Australia Pty Ltd.