



PEL1 SERIES 1

NP-PEL1

Presco™ Event Logger

INTRODUCTION

The Presco™ Event Logger makes programming multiple Presco™ door access controllers a breeze, providing a user friendly platform for access control with full upload/download capabilities directly from your PC.

Maximum security is provided with 3 different operator levels for programming, editing user details or simply viewing events. When an event is logged it is locked into memory and cannot be manipulated, so you know the integrity of your access control system is assured.

FEATURES

12 Volt D.C. operation.

36 month manufacturer's warranty.

800 Users with names up to 32 characters.

Stores 5,000 events with time & date stamping.

Up to 8 Presco™ PAC controllers can be monitored simultaneously giving control of up to 16 doors.

Internal replaceable button cell holds memory and keeps clock running for up to 10 years.

USB 2.0 interface to PC.

PC software supplied for Windows™ Vista, 7 & 8.1.

Three software operator levels restricts to programming features.

SPECIFICATIONS

Dimensions:

104mm x 72mm x 27mm

Operating Voltage:

10 - 15 Volts D.C.

Operating Current:

80 mA. @ 12 Volts D.C.

Supported Controllers:

Series 1 to series 3 PAC1 & PAC2 controllers

PC Interface:

USB 2.0

Weight:

150g

Operating Temperature: 0° to 50°C



Nidac Security

2 Cromwell Street BURWOOD VICTORIA AUSTRALIA 3125

 Phone:
 +61 3 9808 6244

 Fax:
 +61 3 9808 9335

 E-mail:
 sales@nidac.com

 Web:
 www.nidac.com

+12V USB **GND** DLOG1 GND DLOG2 **PRESCO EVENT** DLOG3 LOGGER **GND** DLOG4 Input Voltage 10-15 Volts D.C. DLOG7 DLOG5 **GND GND** DLOG8 DLOG6



